

# Reciprocating Air Compressor Oil

## L-DAB 22, 32, 46, 68, 100, 150

---

### Product Introduction

PetroChina Lubricant Company's L-DAB Reciprocating Air compressor Oil is blended with high quality base oils together with additives to cater to the use in air compressors. It has low tendency in deposits-forming, good thermal oxidation stability, etc. Its quality meets the international standard and requirement.

### Applications

L-DAB compressor oil is suitable for all types of medium and high pressure reciprocating air compressors. It is also suitable for the lubrication and cooling of the variable volume compressors.

### Special Properties

- Excellent thermal stability.
- Good anti-wear properties.
- Excellent demulsibility.
- Suppresses foaming.
- No corrosion to sealing materials or gaskets.

### Bench Test and Mixing Test

- Bench test passed.
- Industrial field test passed.



### **Storage and Precaution**

- All containers, tanks, pipelines and valves has to be cleaned thoroughly and inspected to be clean for use before being used to transfer or transport L-DAB 22, 32, 46, 68,100, 150 to prevent contamination.
- Storage tanks/equipment must be dedicated and is recommended to be stored in an indoor and controlled environment.
- Storage tanks/equipment must be waterproof, mist-proof and free from other mechanical particles.
- Product must be labeled clearly and properly during the entire transportation process to prevent mixing of other petrol-chemical product into the air compressor oil.